


versatile™ 4C Mailbox, 4CADD-07



COMPARTMENT CHART

DESCRIPTION	COMPARTMENT	COMPARTMENT SIZE	QTY.
MAILBOX	MB1	3\" H x 12\" W x 15\" D	7
OUTGOING MAIL	OM2	6-1/2\" H x 12\" W x 15\" D	1
PARCEL	PL5	17\" H x 12\" W x 15\" D	1
PARCEL	PL6	20-1/2\" H x 12\" W x 15\" D	1

Notes:

1. This module meets the USPS STD-4C requirements for installation defined below when the mailbox is installed per the dimensions provided on this drawing.
 - a. At least one customer compartment shall be positioned less than 48\" AFF.
 - b. No parcel locker (interior bottom shelf) shall be positioned less than 15\" AFF.
 - c. No patron (tenant) lock shall be positioned more than 67\" AFF.
 - d. No customer compartment (interior bottom shelf) shall be positioned less than 28\" AFF.
 - e. The USPS Arrow lock shall be positioned 36\"- 48\" AFF.
2. This 4C mailbox can also be used for private applications.
3. The rough opening width for multi-unit 4C installations is provided using the Florence configurator: www.florencemailboxes.com/configurator.

PRODUCT SERIES: VERSATILE™ 4C FRONT LOAD MAILBOX

FLORENCE
CORPORATION

5935 Corporate Drive • Manhattan, KS 66503
 800.275.1747 • www.florencemailboxes.com

MODEL 4CADD-07	REV C
SCALE NONE	LAST REV DATE 06/29/19
DRAWING NUMBER 4CADD-07CS	DRAWN BY RAK