




OUC4


LED Canopy

The OUC4 LED Canopy offers high performance in an economical and practical design. The OUC4 achieves even light distribution using a prismatic, frosted lens that is UV- and fire-resistant while its die-cast aluminum housing has convenient knockouts for easy J-Box, surface mount, or pendant installations. The OUC4 is an efficient outdoor canopy lighting solution for exterior ceilings or for parking garages, carports, covered walkways, or other commercial spaces, and is equipped with an integrated heat sink and a Type V distribution precision lens. The OUC4 offers two models with selectable wattages (75W/60W/45W), (120W/96W/72W) and selectable CCT (3000K/4000K/5000K). Includes factory mounted photocell standard.

Dimensions



75W 9.6 in (243mm)
120W 14 in (356mm)



75W 3.5 in (87.9mm)
120W 5 in (127mm)




FEATURES



Select the Perfect Light

The OUC4 LED Canopy features selectable wattage and color temperature options via an integrated switch.



CRI 70+



Lumens 5527-15547



Lifetime >54000 hrs



Beam Angle 141°-145°

High-Quality Housing

Die-cast aluminum housing with integrated heat sink

Electrical

Integrated 0-10V dimming and 4KV surge protection standard

Precision Optics

High-performance frosted prismatic lens for maximum distribution

Ordering Information

Example: OUC4075SUNVSBZ

Series	Version	Wattage	Voltage	CCTs	Finish	Controls
OUC	4	075S (45W/60W /75W)	UNV (120-277V)	S (3K/4K/5K)	BZ (Bronze)	_Blank (Photocell)
		120S (72W/96W/120W)			WH (White)	S (12V 3.5mm Socket)

See spec-sheet for additional ordering information.