

DLR56v5 System

6" Recessed LED Downlight + Frame

Product Description

The DLR56v5 System from NICOR is a 6" recessed LED downlight and frame combination that is ideal for new construction installations. Minimizing overall system cost while maximizing performance, the DLR56v5 System is the perfect solution for new construction in residential and light commercial spaces.

System Construction

- Spun aluminum trim routes heat away from electrical components
- Ultra low profile, integrated driver
- Patented trim attachment system with IDEAL connector
- Heavy-gauge NICOR captive hanger bars provide greater stability, allowing housing to be positioned at any point within a 24" joist span, then locked in place with set screws
- Swivel foot on one end of hanger bars ease single person installation
- Airtight system

Electrical

- Dimmable to 5% with compatible TRIAC dimmers
- Operating temperature rating of 0°F to 120°F (-18°C to 49°C)
- Input voltage of 120VAC
- Lifetime rated for greater than 60,000 hours
- LM-79 testing performed in accordance with IESNA standards
- Meets FCC Part 15, Subpart B, Class B standards for conducted and radiated emissions.

Trim Finish

- Exterior white powder coat finish
- Available accessory trim covers in Black, Oil-Rubbed Bronze and Nickel
- Baffle available

Warranty

- 5-year limited system warranty

For additional information please see the individual specsheets for the DLR56v5 Downlight and DLR56-5-FRAME at www.nicorlighting.com

Project

Catalog

Type

Date



Except 5000K

Patent Pending

Ordering Information

Example: DLR56v5SYS083KWH

v	System	Lumens	CCT's	Trim Color	Baffle
DLR56	5SYS	08 (800 lm)	2K (2700 K)	WH (White)	(Blank)
		12 (1200 lm)	3K (3000 K)		BF (Baffle)
			4K (4000 K)		
			5K (5000 K)		

Specifications and dimensions subject to change without notice.

