



EXL1



EXL1-SELECT

CONSTRUCTION

Injection molded thermoplastic ABS housing
 UL-94V-0 flame rating - Flame Retardant
 Red or Green text options available
 6" Letter Height
 Single or Double Face Configuration

Injection molded thermoplastic ABS housing
 UL-94V-0 flame rating - Flame Retardant
Field Selectable Red and Green LED light and lettering
 6" Letter Height
 Single or Double Face Configuration

ELECTRICAL

120/277V Dual Voltage Operation
 LED Indicator Light & Push Button Test Switch
 90 Min capacity on emergency mode
 Damp Location Rated
 Operating temperature rating of 32°F to 104°F (0°-40° C)

120/277V dual voltage operation
 LED indicator light & push-button test switch
 90 Min capacity on emergency mode
 Damp location rated
 Operating temperature rating of 32°F to 104°F (0°-40°c)

OTHERS

Input Voltage (V): 120/277VAC
 Input Power (W): 3.8W
 Charging Time: 24 hrs
 Emergency Battery Run Time: 90 minutes
 System Warranty: Year Limited

Input Voltage (V): 120/277VAC
Input Power (W): 1W
 Charging Time: 24 hrs
 Emergency Battery Run Time: 90 minutes
 System Warranty: 1 Year Limited



DIMENSIONS

