



HBC5 LED High-Bay Comparison



	HBC5	Keystone
MODELS AVAILABLE	HBC5150SUS8(BK,WH) HBC5240SUS8(BK,WH)	KT-RHLED150PS-12C-8CSB-VDIM-P KT-RHLED200PS-14C-8CSB-VDIM-P KT-RHLED400PS-18C-8CSD-VDIM-P
WATTAGE SELECTABLE?	Yes	Yes
WATTAGES AVAILABLE	100W/120W/150W 200W/220W/240W	70W/100W/150W 100W/150W/200W 240W/320W/400W
CCT SELECTABLE?	Yes	Yes
CCTS AVAILABLE	3500K/4000K/5000K	3000K/4000K/5000K (150W and 200W) 4000K/5000K (400W)
VOLTAGE INPUT	120-277VAC	120-277VAC (480VAC xfmr available)
SURGE SUPPRESSION	6kV/3kA	6kV
FINISH COLOR	Black, White	Black
OPTICAL ACCESSORIES	Aluminum Reflector Polycarbonate Reflector Polycarbonate Glare Shield Wire Guard	(150W models only) Aluminum Reflector Polycarbonate Reflector w/ Glare Shield Wire Guard
MOUNTING & ACCESSORIES	J-Hook with Locking Bolt (standard) Pendant Adapter (BK/WH) Yoke Mount (BK/WH)	Ring-Bolt (150 and 200W) J-Hook (400W) Yoke (150W model only) Junction Box
EMERGENCY PACK	EMB400 (40W)	40W
CONTROLS CAPABILITY	12VDC output lead, On-board sensor socket (PIR, Microwave, NLC (Bluetooth))	On-board sensor socket (PIR, Microwave, Bluetooth)
DIMENSIONS	Diameter Height 11.0" 6.7" (150W) 13.4" 7.5" (240W)	Diameter Height 12.6" 6.7" (150W) 14.8" 7.7" (200W) 17.7" 15.8" (400W)
TEMP RATING	-40°F - 122°F	-40°F - 122°F (150W and 200W) -40°F - 140°F (400W)
CERTIFICATIONS	   	   