

# VT4

# COMPARISON SHEET



	VT3-20		VT4
INPUT VOLTAGE	120-277VAC		120-277VAC
CCT OPTIONS	Single CCT Only: 4000K or 5000K		Selectable: <span>3.5K</span> <span>4K</span> <span>5K</span>
WATTAGE OPTIONS	Standard Output (4S) 38W	High Output (4H) 52W	Selectable: <span>34W</span> <span>38W</span> <span>45W</span>
DELIVERED LUMENS	4,952 - 4,992 Lm	6,724 - 6,778 Lm	5364 - 7964 Lm
SYSTEM EFFICACY	130 Lm/W	130 Lm/W	134 - 152 Lm/W
DLC	DLC 5.1 Standard		DLC 5.1 Standard
LENS	Wrapped Polycarbonate		Wrapped Polycarbonate
12V ACCESSORY PORT	Not Available		12VDC Accessory Port
DIMMING	0-10VDC (down to 10%)		0-10VDC (Dim-to-Off)
OPERATING TEMPERATURE	-40°F to 122°F (-40°C to 50°C)		Surface Mounted: -40°F to 113°F (-40°C to 45°C) Suspended: -40°F to 122°F (-40°C to 50°C)*
MOTION SENSOR	Not Available		Microwave Sensor Available
MOUNTING OPTIONS	Surface Mount and Suspension Cable Mount		Surface Mount and Suspension Cable Mount
BATTERY BACKUP	8W and 16W Options*		8W and 18W Options
WARRANTY	5-Year Limited		5-Year Limited
CERTIFICATIONS			

\* Emergency pack only available on 4' and 8' versions.

\* When suspended at least 18" from ceiling.