



| | DCGv3 | | DCGv2 | | DLGv1 | |
|--------------------|-------------------------|----------|------------------------|----------|-------------------------------------|----------|
| FINISHES AVAILABLE | White, Black | | White | | Black Oil-Rubbed Bronze White | |
| DIMENSIONS | DCG4 | DCG6 | DCG4 | DCG6 | DCG4 | DCG6 |
| Radius | 5 in | 7.2 in | 5 in | 7.25 in | 5 in | 7 in |
| Height | 2.7 in | 2.9 in | 3.2 in | 4.1 in | 3.4 in | 3.3 in |
| WATTAGES | DCG4 | DCG6 | DCG4 | DCG6 | DCG4 | DCG6 |
| | 7.4 W | 9.4 W | 7.5 W | 10.4 W | 9.1 W | 12.5 W |
| LUMEN OUTPUT | DCG4 | DCG6 | DCG4 | DCG6 | DCG4 | DCG6 |
| | 700 lm | 900 lm | 500 lm | 800 lm | 600 lm | 1000 lm |
| CCT SELECTABLE | select | | NO | | NO | |
| CCTS AVAILABLE | 27K/30K/45K/40K/50K | | 27K, 30K, 40K, 50K | | 27K, 30K, 40K | |
| EFFICIENCY (LM/W) | DCG4 | DCG6 | DCG4 | DCG6 | DCG4 | DCG6 |
| | >97 lm/W | >97 lm/W | >70 lm/W | >80 lm/W | >65 lm/W | >80 lm/W |
| VOLTAGE | 120 VAC | | 120 VAC | | 120 VAC | |
| TILT | 30° | | 35° | | 35° | |
| ROTATION | DCG4 | DCG6 | DCG4 | DCG6 | DCG4 | DCG6 |
| | 350° | 354° | 359° | 354° | 360° | 360° |
| BEAM DISTRIBUTION | DCG4 | DCG6 | DCG4 | DCG6 | DCG4 | DCG6 |
| | 90° | 99° | 113° | 113° | 105° | 98° |
| CERTIFICATIONS | *Except 5000K | | *Except 5000K | | *Except DLG2 | |
| LIFESPAN (L70) | 54,000 hours | | 56,000 hours | | >36,000 hours | |