

Integrated LED Tubes

Type A High CRI Glass Tubes with
TriGain® Technology

Project Name _____

Date _____ Type _____

Notes _____

Unlike most LED Lamps, Current's High CRI LED Tube utilizes TriGain® Technology to enhance color rendering without decreasing efficiency. An ideal solution for retailers and others seeking high CRI without compromising on energy efficiency. Current's Type A integrated LED tubes run on electronic T8 instant-start or programmed start ballasts.



PERFORMANCE HIGHLIGHTS:

| Type A High CRI Glass Tubes | |
|-------------------------------------|--|
| Light Output Range: | 1300-2250 Lumens |
| CRI: | 90 |
| CCT: | 3500K, 4500K & 5000K |
| Wattage: | 9-15W |
| Life: | 70,000 hours L70 |
| Temperature Rating: | -20°C to 40°C |
| Rating: | Damp |
| Fixtures: | Open or Enclosed |
| Dimming: | Dimmable with compatible dimming ballasts |
| Ballast Compatability Guide: | gecurrent.com/LEDTUBES-ballastcompatibility |
| Certification: | DLC Listed |

LIMITED WARRANTY

7 Years

BENEFITS:

- Better quality of light
 - >90 CRI provides overall superior color quality
 - >50 R9 provides vivid reds
 - Best option for displaying merchandise
- Fast and Easy LED upgrade
- 2.3X longer life than LFL (70,000 vs. 30,000 hours)
- Better quality of light-instant on
- Low energy LFL replacement
- Easy disposal, non-hazardous waste

LEARN MORE:

To learn more about saving money and energy, go to www.gecurrent.com.

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.



DIMMABLE



DAMP RATED



Integrated LED Tubes

Type A High CRI Glass Tubes with TriGain® Technology

Spec Table

Project Name _____

Date _____ Type _____

Notes _____

Integrated Glass Tubes with TriGain® Technology - Type A

| Base Type | Order Type | Watts | Code | Description | Low BF Watts | Normal BF Watts | High BF Watts | Case Qty** | MOL (In) | Lumens Initial | Initial Color Temp | CRI | *Rated Life L70 (Hrs) | DLC® | UL | # Location Rating | Additional Information |
|---|------------|-------|-------|------------------|--------------|-----------------|---------------|------------|----------|----------------|--------------------|-----|-----------------------|------|-----|-------------------|------------------------|
| Integrated 4 ft High CRI with TriGain® Technology LED Glass Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | | |
| T8 | G13 | 15 | 34307 | LED15ET8/G/4/935 | 13.5 | 15 | 21.5 | 20 | 48 | 2150 | 3500K | 90 | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 15 | 34313 | LED15ET8/G/4/940 | 13.5 | 15 | 21.5 | 20 | 48 | 2200 | 4000K | 90 | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| | G13 | 15 | 34316 | LED15ET8/G/4/950 | 13.5 | 15 | 21.5 | 20 | 48 | 2250 | 5000K | 90 | 70,000 | Yes | Yes | Damp | Instant or PRS Ballast |
| Integrated 3 ft High CRI with TriGain® Technology LED Glass Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | | |
| T8 | G13 | 11 | 34323 | LED11ET8/G/3/935 | 9.5 | 11 | 15 | 20 | 36 | 1500 | 3500K | 90 | 70,000 | - | Yes | Damp | Instant or PRS Ballast |
| | G13 | 11 | 34326 | LED11ET8/G/3/940 | 9.5 | 11 | 15 | 20 | 36 | 1500 | 4000K | 90 | 70,000 | - | Yes | Damp | Instant or PRS Ballast |
| | G13 | 11 | 34332 | LED11ET8/G/3/950 | 9.5 | 11 | 15 | 20 | 36 | 1600 | 5000K | 90 | 70,000 | - | Yes | Damp | Instant or PRS Ballast |
| Integrated 2 ft High CRI with TriGain® Technology LED Glass Tubes (operates on Instant Start or Program Start Ballast) | | | | | | | | | | | | | | | | | |
| T8 | G13 | 9 | 34337 | LED9ET8/G/2/935 | 8 | 9 | 13 | 20 | 24 | 1300 | 3500K | 90 | 70,000 | - | Yes | Damp | Instant or PRS Ballast |
| | G13 | 9 | 34341 | LED9ET8/G/2/940 | 8 | 9 | 13 | 20 | 24 | 1300 | 4000K | 90 | 70,000 | - | Yes | Damp | Instant or PRS Ballast |
| | G13 | 9 | 34342 | LED9ET8/G/2/950 | 8 | 9 | 13 | 20 | 24 | 1400 | 5000K | 90 | 70,000 | - | Yes | Damp | Instant or PRS Ballast |

Information provided is subject to change without notice. Please verify all details with Current. All values are design or typical values when measured under laboratory conditions, and Current makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

* The life rating is based on the hours of operation the lamp will provide before reaching 70% of its original rating (L70)

** Minimum order quantity = 6

UL 1993 Environmental Requirements for LED LAMPS

Location, damp – Exterior or interior location that is normally or periodically subject to condensation of moisture in, on, or adjacent to, electrical equipment, and includes partially protected locations.
 Location, dry – Location not normally subject to dampness, may include a location subject to temporary dampness, i.e., building under construction, provided ventilation is adequate to prevent an accumulation of moisture.

Location, wet – Location in which water or other liquid can drip, splash, or flow on or against electrical equipment.

Notes: 1) Product descriptions ending in "/TP" indicate a carded blister or clamshell package nested in a tray for shelf display. Cards also designed for hook display.