

COMPETITIVE COMPARISON
LED Prismatic Wrap



NICOR

RAB

Fixture	WPP	GUS®JR
Length	4 foot	2 foot, 4 foot
Input Voltage	120-277VAC	120-277VAC
CCT Options	5 Color Selectable 3000/4000/5000/5700/6500K	3 Color Static 3000 or 4000 or 5000K
Wattage Options	Selectable - 21/26/34/40W	Static - 2 ft: 20W; 4 ft: 27W or 40W
Delivered Lumens	Selectable - 3451/4137/5256/6379	2 ft: 2620, 4 ft: 3457 or 4834
System Efficiency	152 - 171	114 - 131
DLC	DLC5.1 Standard listed for Linear Ambient	DLC5.1 Standard
Dimming Range	0 - 10 VDC (Full Range)	0 - 10 VDC (Full Range)
Operating Temperature	-4°F to 122°F (-20° to 50°C)	-4°F to 104°F (-20° to 40°C)
TM-21 L70 LIFESPAN	>50,000	>50,000
Motion Sensor	Yes. Microwave Option behind lens	Yes. External Lightcloud®
Mounting Options	Surface Mount, Suspension Cable Mount, Endcap KOs	Surface Mount, Hook and Chain, Endcap KOs, Through Wire Kit
Battery Backup	Yes. 8W EM	Yes (4ft model with Lightcloud only)
Warranty	5-Year Limited	5-Year Limited