



8600

NOSE BOND®

STAIR NOSE ADHESIVE



Powered by Microban® for superior mold and mildew protection.

1. DESCRIPTION

ROBERTS® 8600 NOSE BOND® is specifically designed for interior stair nose installations on properly prepared wood subfloors. Use with wood, laminate, and rigid PVC stair nose used with vinyl floors.

Features and Benefits

- Ideal for wood, laminate and rigid PVC stair nosing
- Can also be used for wood moldings, wood trim installs and repairs
- Easy clean up
- Commercial and residential use
- Coverage up to 30 lineal feet / per 10 oz cartridge
- Powered by Microban® for superior mold and mildew protection

Approved Flooring Types

Stair Nose - Wood, laminate and rigid PVC stair nose used with vinyl floors

For floorings and backings not listed, contact Technical Services at (706) 277-5294 (U.S.A) and (905) 791-4444 (CA).

2. TECHNICAL DATA

Product Type:	Advanced Acrylic Adhesive
Color:	Beige
Odor:	Very mild, non-offensive
Open Time:	Up to 20 minutes
Working Time:	Up to 30 minutes Setup time will vary slightly with temperature and porosity of substrate
Curing Time:	8-10 hours
Traffic:	Residential: 24 hours Commercial: 24 hours Rolling Loads: N/A
Shelf Life:	2 years from date of manufacture when stored in the original unopened container in a controlled environment. Does not require thinning
Storage:	Protect from freezing
VOC:	2 g/L



SHELF LIFE
2 YEARS

3. INSTRUCTIONS

Limitations

- For interior installations only
- Not recommended over non-porous materials or painted surfaces
- Concrete and plaster must be properly seasoned and dry prior to installation

Preparation

Surface must be clean, dry and free of contaminants that might interfere with the bond or the installation.

Installation

Apply a serpentine pattern bead to the underside of the stair nose, and a bead along the inside front edge. Press into place. Apply mechanical fasteners (as needed) per manufacturer's guidelines.

Clean-up

Fresh adhesive – warm, soapy water on a clean cloth.

Dried adhesive – use mineral spirits sparingly with a clean, white cotton cloth.

4. AVAILABILITY

USA		
10 oz Tube	8600-10C	075378716013



Canada		
295 mL Tube	8600-10C	075378716013



5. WARRANTY

Roberts Consolidated Inc. offers a limited-product warranty on this product when installed in accordance with the printed specifications.

Visit robertsconsolidated.com, robertsconsolidated.com/ca or call (866) 435-8665 for full warranty details.

6. TECHNICAL SERVICES

For technical assistance or installation questions not covered in this document, please contact our Technical Services Department at (706) 277-5294 U.S.A. / (905) 791-4444 Canada.



Adhesive Made in the USA - Container sourced domestically & internationally.

ROBERTS® and the e® logo are registered trademarks of Roberts Consolidated Industries, Inc. • Q.E.P.® is a registered trademark of Q.E.P. Co., Inc. LEED® and its related logo, is a trademark owned by the U.S. Green Building Council® • Microban® is a registered trademark of Microban Products Company.

J0126-01374



Roberts Consolidated Industries, Inc.
300 Cross Plains Blvd, Dalton, GA 30721
Customer Service: (866) 435-8665
Technical Support: (706) 277-5294
robertsconsolidated.com



Roberts Company Canada, Ltd.
34 Hansen Road, Brampton, ON L6W 3H4
Customer Service: (866) 435-8665
Technical Support: (905) 791-4444
robertsconsolidated.com/ca

