

# DLG4

## 4" LED Downlight Gimbal

The DLG4 is the perfect LED downlight for directional accent lighting. Its easy to use twist-and-turn design allows for fine adjustment of the gimbal position. The 360 degrees of rotation and 35 degrees of adjustable tilt in both directions makes the DLG suitable for sloped ceilings and wall wash. The sleek design enhances any interior space with its flush mounting and aesthetic appeal.

**Aperture:** Available in round

**CCT:** 2700K, 3000K, or 4000K

**High Performing LEDs:** Greater than 90 CRI; R9 greater than 50

**Reported Lifetime:** Greater than 36,000 Hours

**Power Draw:** 9.1W

**Input Voltage:** 120V

**Dimmable:** To less than 10% with most standard TRIAC dimmers

**Operating temperature:** 0° to 120°F (-18°C to 49°C)

**Installation:** Easy installation with a screw-in Edison base and friction clip mounting system

### Finish Options



WHITE



OIL-RUBBED BRONZE




**NICOR**® | **LED**

# DLG4 | 4" LED Downlight Gimbal

## Photometric Data

### DLG4 2700K

Input Voltage (VAC)	120V
System Level Power (W)	9.1
Delivered Lumens (Lm)	597
System Efficacy (Lm/W)	65.5
Correlated Color Temp (K)	2777
Color Rendering Index (CRI)	95
Beam Angle	105°
Spacing Criteria	1.21



### Intensity Summary (Candle Power)

Angle	Mean CP
0	226
5	225
15	215
25	195
35	167
45	135
55	101
65	67
75	37
85	14
90	5

### CCT Data Multiplier

DLG4-10-120-3K	1.025
DLG4-10-120-4K	1.055

### Cone of Light Tabulation

Mounted height (Feet)	Footcandles Beam Center	Diameter (Feet)
4	14.1	4.9
6	6.3	7.2
8	3.5	9.8
10	2.3	11.7
12	1.6	14.0
14	1.2	16.0
16	0.9	19.0

### Zonal Lumen Summary

Zone	Lumens	% of Luminaire
0-30	172	28.7%
0-40	276	46.2%
0-60	470	78.7%
0-90	591	99.0%
90-180	6	1.0%
0-180	597	100.0%

Fixture tested per LM-79-08. Photometric data is of the performance of a representative fixture. Results may vary in the field.

### Performance Data

Model Number	Lumens	Watts	Lumens/Watt
DLG4-10-120-3K	597	9.1	65.5
DLG4-10-120-3K	612	9.1	67.1
DLG4-10-120-4K	630	9.1	69.1

### Recommended Dimmers\*

Lutron Toggler TGCL-153P  
 Lutron DIVA DVELV-300P  
 Lutron DIVA DVELV-303P  
 Lutron Skylark SELV-300P  
 Leviton C22-06672-1LW

### Housing Compatibility\*

19000A-LED-ID 4" LED IC AIRTIGHT NEW CONSTRUCTION HOUSING  
 19001AR-LED-ID 4" LED IC AIRTIGHT REMODEL HOUSING  
 MOST STANDARD 4" RECESSED HOUSINGS

\*Not a complete list. Check compatibility before installation.

## Ordering Information

Series	Version	Voltage	CCT's	Trim Color
DLG4	10 (Version 1)	120 (120V)	2K (2700 K)	WH (White)
			3K (3000 K)	OB (Oil-rubbed Bronze)
			4K (4000 K)	

## Accessories

Accessories sold separately

GU24 Socket String

GU24-IDEAL-SKT-STR

## Dimensions

