



PREMIUM CORK UNDERLAYMENT ROLLS 110650

INSULATING

Reduces thermal transmission, increasing effectiveness of floor heating systems

R-Value
0.74

CRACK SUPPRESSION

Acts as a crack isolation membrane that resists transfer of stress cracks from subfloor through to flooring surfaces

SOUND ABSORBING

Reduces sound transmission from both the surface of a floor as well as through the floor to living spaces below

EASY TO INSTALL

In both glue-down and loose lay configurations**

IIC STC Δ
74* | 70* | 22

*Ceramic tile on a 6" concrete slab with a suspended ceiling

VERSATILE

For use under ceramic tile, stone, marble, glued wood flooring and floating floor systems



**For a list of recommended adhesives to use for glue-down installations, please go to capitolflooringproducts.com or call 866-435-8665.

ITEM #	DESCRIPTION	QTY	SIZE	COVERAGE
110650	1/4" (6 mm) Roll	1 Roll	48"x25'	100 ft ² / roll

Our Premium Cork products may contribute towards satisfying credits under the LEED[®] Green Building Program in the following areas:

MR 4.1 - 5% Recycled Content of total building materials (post consumer + ½ of post industrial)

MR 4.2 - 10% Recycled Content of total building materials (post consumer + ½ of post industrial)

MR 6 - Specifying rapidly renewable building materials for 5% of total building materials.

EQ 4.1 - Low Emitting Materials Adhesives & Sealants (Adhesives Specified meet SCAQMD Rule 1168)



CERTIFIED BY
SCS Global Services