


Specifications	IXE Series	REL Series	REL-Select Series	REL-Regressed Series	REL-UNV Series
Product Images					
Model Numbers	IXE41120S8RDBK-12PK IXE41120S8RDWH-12PK IXE61120S8RDBK-12PK IXE61120S8RDWH-12PK	REL411202KRDWH REL411203KRDWH REL411204KRDWH REL411205KRDWH REL611202KRDWH REL611203KRDWH REL611204KRDWH REL611205KRDWH REL811202KRDWH REL811203KRDWH REL811204KRDWH REL811205KRDWH	REL411205RDWH REL411205SQWH REL611205RDWH REL611205SQWH	REL41120SRRWH REL41120SQRWH REL61120SRRWH REL61120SQRWH	REL611UNVSRDWH REL611UNVSRDWHBF
Sizes	4" / 6"	4" / 6" / 8"	4" / 6"	4" / 6"	6"
Dimensions	4": 4.92in x 4.92in x 0.83in 6": 6.7in x 6.7in x 0.83in	4": 4.7in x 4.7in x 0.9in 6": 6.7in x 6.7in x 0.9in 8": 8.9in x 8.9in x 0.9in	4" Round: 5.0in x 5.0in x 0.87in 4" Square: 4.7in x 4.7in x 0.91in 6" Round: 7.2in x 7.2in x 0.83in 6" Square: 6.7in x 6.7in x 0.91in	4": 4.7in x 4.7in x 1.37in 6": 6.7in x 6.7in x 1.37in	6.8in x 6.8in x 0.7in
Material	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum	Cast Aluminum
Color Options	4": White, Black 6": White	White	White	White	White
Finish/Shape	Smooth/Round	Smooth/Round	Smooth/Round or Square	Baffle/Round or Square	Smooth or Baffle/Round
Faceplate Options	4": Black, Oil-Rubbed Bronze  6": Black, Nickel, Oil-Rubbed Bronze 	Black, Nickel, Oil-Rubbed Bronze 	Black, Oil-Rubbed Bronze (Round only) 	None	None
Voltage	120VAC	120VAC	120VAC	120VAC	120-277VAC
Wattage	4": 8.8W 6": 11.8W	4": 10.3W 6": 11.8W 8": 17.9W	4": 10.3-10.8W 6": 12.0-12.8W	4": 10.1-10.8W 6": 11.8-12.8W	12.6W
Lumens	4": 505-621Lm 6": 922-1097Lm	4": 666-717Lm 6": 902-971Lm 8": 1279-1376Lm	4": 612-905Lm 6": 816-1127Lm	4": 612-768Lm 6": 816-1019Lm	985-1137Lm
Lumens/Watt	4": 58.0-73.6Lm/W 6": 78.1-96.2Lm/W	4": 64.7-69.6Lm/W 6": 76.4-82.3Lm/W 8": 71.5-76.9Lm/W	4": 59.5-85.1Lm/W 6": 68.1-89.7Lm/W	4": 59.5-72.1Lm/W 6": 68.1-81.5Lm/W	77.9-90.0Lm/W
Technology	CCT Select	Single CCT	CCT Select	CCT Select	CCT Select
CCT					
CRI (R9)	>80 (>50)	>90 (>50)	>90 (>50)	>90 (>50)	>90 (>50)
Operating Temp.	-4°F to 113°F (-20°C to 45°C)	-4°F to 104°F (-20°C to 40°C)	-4°F to 104°F (-20°C to 40°C)	-4°F to 104°F (-20°C to 40°C)	-4°F to 104°F (-20°C to 40°C)
Dimmable	TRIAC (to 10%)	TRIAC/ELV (to 5%)	TRIAC/ELV (to 5%)	TRIAC/ELV (to 5%)	TRIAC/ELV/0-10V (to 5%)
Lifespan (L70)	>50,000 Hours	>54,000 Hours	>54,000 Hours	>54,000 Hours	>54,000 Hours
Warranty	5 Years 	5 Years 	5 Years 	5 Years 	5 Years 
Certifications					