



	OWF4	OWF5
SPEC-SHEET	View Spec-Sheet	View Spec-sheet
MODEL NUMBERS	OWF4080SMVSBZ	OWF5040SUS8BZS OWF5100SUS8BZS OWF5150SUS8BZS
DIMENSION	14.21in x 6.57in x 9.29in	8.3in x 6.69in x 5.43in 13.34in x 8.26in x 5.86in 16.93in x 10.63in x 7.13in
HOUSING MATERIAL	Die-cast aluminum	Die-cast aluminum
LENS MATERIAL	injection -molded acrylic	injection -molded acrylic
COLOR OPTIONS	Bronze	Bronze
TYPE	Integrated LED	Integrated LED
VOLTAGE	120-277VAC	120-277VAC
WATTAGE	40W 60W 80W	20W 30W 40W 60W 80W 100W 90W 120W 150W
LUMEN OUTPUT	5,237 - 11,294 Lm	2,864 - 24,409 Lm
TECHNOLOGY	Wattage/CCT Select	Wattage/CCT/Light Distribution Select
CCT OPTIONS	3K 4K 5K	3K 4K 5K
CRI	>70	>80
OPERATING TEMPERATURE	-40°F to 122°F (-20°C to 50°C)	-40°F to 113°F (-40°C to 45°C)
DIMMING	0-10V	0-10V
LIFESPAN (L70)	>51,000 Hours	>54,000 Hours
WARRANTY	5 YEAR WARRANTY	5 YEAR WARRANTY
EMERGENCY BACKUP	Yes	Yes
DLC	5.1 Premium	6.0 Premium
CERTIFICATES & LISTINGS	     	     