



HBC5 LED High-Bay Comparison



	HBC5	Keystone
MODELS AVAILABLE	HBC5150SUS8(BK,WH) HBC5240SUS8(BK,WH) HBC5300SUS8(BK,WH)	KT-RHLED150PS-12C-8CSB-VDIM-P KT-RHLED200PS-14C-8CSB-VDIM-P KT-RHLED400PS-18C-8CSD-VDIM-P
WATTAGE SELECTABLE?	Yes	Yes
WATTAGES AVAILABLE	100W/120W/150W 200W/220W/240W 240W/270W/300W	70W/100W/150W 100W/150W/200W 240W/320W/400W
CCT SELECTABLE?	Yes	Yes
CCTS AVAILABLE	3500K/4000K/5000K	3000K/4000K/5000K (150W and 200W) 4000K/5000K (400W)
VOLTAGE INPUT	120-277VAC 277-480VAC	120-277VAC (480VAC xfmr available)
SURGE SUPPRESSION	6kV/3kA	6kV
FINISH COLOR	Black, White	Black
OPTICAL ACCESSORIES	Aluminum Reflector Polycarbonate Reflector Polycarbonate Glare Shield Wire Guard	(150W models only) Aluminum Reflector Polycarbonate Reflector w/ Glare Shield Wire Guard
MOUNTING & ACCESSORIES	J-Hook with Locking Bolt (standard) Pendant Adapter (BK/WH) Yoke Mount (BK/WH)	Ring-Bolt (150 and 200W) J-Hook (400W) Yoke (150W model only) Junction Box
EMERGENCY PACK	EMB4002 (40W)	40W
CONTROLS CAPABILITY	12VDC accessory output, Onboard sensor socket (PIR, Microwave, NLC (Bluetooth))	Onboard sensor socket (PIR, Microwave, Bluetooth)
DIMENSIONS	Diameter Height 11.0" 6.7" (150W) 13.4" 7.5" (240W) 13.8" 9.6" (300W)	Diameter Height 12.6" 6.7" (150W) 14.8" 7.7" (200W) 17.7" 15.8" (400W)
TEMP RATING	-40°F to 122°F -22°F to 122°F (with Sensor)	-40°F to 122°F (150W and 200W) -40°F to 140°F (400W)
CERTIFICATIONS	   	   