



POLLUS - OTL

LED Pole Top

Pollus provides even illumination with advanced LED technology, making it the ideal pole top lighting solution for exterior pathways, courtyards, and parking lots. Pollus features a polycarbonate precision lens in a Type V "very short" distribution and is easily mounted to a 3" diameter pole using a 2 3/8" tenon adapter. The bronze LED pole top is available in 40W and 80W with a 5000K color temperature and has photocell and motion sensor options to suit your environment. The fixture is also dimmable from 0-10VDC and includes 10kA surge protection.

- Thermally-protected, high-efficiency driver
- High-impact, polycarbonate precision lenses in Type II, Type III, Type IV, and Type V distributions
- Operating temperature rating of -4° to 104°F (-20°C to 40°C)
- 10kA surge protection standard
- Input voltage of 120-277VAC
- Available in 40W and 85W
- Driver delivers full-range dimming from 0 – 10VDC



5000K

5000K



4127Lm

7358Lm



40W

85W



115

100



OPL

3" & 4" Poles

The OPL are poles designed to fit the Aquila OAL area light fixtures as well as the Pollus OTL Poletop fixture.

- Straight steel construction with 3" round, 4" round, and 4" square options available
- General purpose pole for up to 12' (3" Pole) and up to 25' (4" Poles) mounting heights
- 3" Pole available in lengths of 8', 10', and 12'
- 4" Pole available in lengths of 15' and 25'
- Pole shaft is from weldable grade cold rolled, commercial quality carbon steel tubing conforming to ASTM-A500 grade B 11 gauge
- All welds conform to AWS D1.2 using ER70s-6 electrodes
- Grounding Provision incorporating a tapped 1/2"-13NC hole welded to frame

