



	DCGv3			DCGv2			DLGv1		
FINISHES AVAILABLE	White, Black			White			Black Oil-Rubbed Bronze White		
DIMENSIONS		DCG4	DCG6		DCG4	DCG6		DLG4	DLG6
	Radius	5 in	7.2 in	Radius	5 in	7.25 in	Radius	5 in	7 in
	Height	2.7 in	2.9 in	Height	3.2 in	4.1 in	Height	3.4 in	3.3 in
WATTAGES		DCG4	DCG6		DCG4	DCG6		DLG4	DLG6
		7.4 W	9.4 W		7.5 W	10.4 W		9.1 W	12.5 W
LUMEN OUTPUT		DCG4	DCG6		DCG4	DCG6		DLG4	DLG6
		700 lm	900 lm		500 lm	800 lm		600 lm	1000 lm
CCT SELECTABLE	select			NO			NO		
CCTS AVAILABLE	 27K/30K/45K/40K/50K			 27K, 30K, 40K, 50K			 27K, 30K, 40K		
EFFICIENCY (LM/W)		DCG4	DCG6		DCG4	DCG6		DLG4	DLG6
		>97 lm/W	>97 lm/W		>70 lm/W	>80 lm/W		>65 lm/W	>80 lm/W
VOLTAGE	120 VAC			120 VAC			120 VAC		
TILT	30°			35°			35°		
ROTATION		DCG4	DCG6		DCG4	DCG6		DLG4	DLG6
		350°	354°		359°	354°		360°	360°
BEAM DISTRIBUTION		DCG4	DCG6		DCG4	DCG6		DLG4	DLG6
		90°	99°		113°	113°		105°	98°
CERTIFICATIONS	 *Except 5000K			 *Except 5000K			 *Except DLG2		
LIFESPAN (L70)	54,000 hours			56,000 hours			>36,000 hours		