









	DCRv3	DLR56P	DLRv6	DLRv7
				
Sizes	4in, 5/6in	5/6in	4in, 5/6in	4in, 5/6in
Trims	Smooth, Baffled	Smooth, Baffled	Smooth, Baffled	Smooth, Baffled
Finish	Matte White	Matte White	White Powder Coat	White Powder Coat
Material	Polymer Housing / Polycarbonate Diffuser	Polymer Housing / Polycarbonate Diffuser	Steel Housing / Polymer Driver Cover	Steel Housing / Polymer Driver Cover
Voltage	120VAC	120VAC	120VAC	120VAC
Lumens	4in: 719-764 Lm 5/6in: 895-945 Lm	5/6in: 895-945 Lm	4in: 721-758 Lm 5/6in: 918-962 Lm 5/6in (HO): 1224-1248 Lm	4in: 600 750 900 5/6in: 900 1200 1500
CRI	95 CRI (R9=76)	95 CRI (R9=76)	94 CRI (R9=68)	>90
CCT	27K 30K 35K 40K 50K	27K 30K 35K 40K 50K	27K 30K 35K 40K 50K	27K 30K 35K 40K 50K
Lumens/Watt	4in: 99-106 Lm/W 5/6in: 97-103 Lm/W	5/6in: 97-103 Lm/W	4in: 91-99 Lm/W 5/6in: 89-95 Lm/W 5/6in (HO): 88-93 Lm/W	4in: >112.5 Lm/W 5/6in: >107 Lm/W
Wattage	4in: 7.2W 5/6in: 9.2W	5/6in: 9.2W	4in: 7.5W 5/6in: 10W 5/6in (HO): 13W	4in: 5-8W 5/6in: 8-14W
Dimmable	10% TRIAC/ELV	10% TRIAC/ELV	5% TRIAC/ELV	5% TRIAC/ELV
Fixture Depth	4in: 1.47" (37.5mm) 5/6in: 1.8" (45.9mm)	5/6in: 2.5" (63mm)	4in: 2.7" (69mm) 5/6in: 3.5" (89mm)	4in: 2.7" (69mm) 5/6in: 3.5" (89mm)
Color Options	WHITE	WHITE	WHT, BK, NK, OB	WHT, BK, NK, OB
Certifications				
Installation	Most Standard Housings	Patented DLR56-FRAME	Patented DLR56-FRAME	Patented DLR56-FRAME