



VERSION COMPARISON Recessed LED Gimbals



	DCGv3		DCGv2		DLGv1	
FINISHES AVAILABLE	White		White		Black Oil-Rubbed Bronze White	
DIMENSIONS		DCG4	DCG6		DCG4	DCG6
	Radius	5 in	7.2 in	Radius	5 in	7 in
	Height	2.7 in	2.9 in	Height	3.2 in	4.1 in
WATTAGES		DCG4	DCG6		DCG4	DCG6
		7.4 W	9.4 W		7.5 W	10.4 W
LUMEN OUTPUT		DCG4	DCG6		DCG4	DCG6
		700 lm	900 lm		500 lm	800 lm
CCT SELECTABLE	select		NO		NO	
CCTS AVAILABLE						
	27K/30K/45K/40K/50K		27K, 30K, 40K, 50K		27K, 30K, 40K	
EFFICIENCY (LM/W)		DCG4	DCG6		DCG4	DCG6
		>97 lm/W	>97 lm/W		>70 lm/W	>80 lm/W
VOLTAGE	120 VAC		120 VAC		120 VAC	
TILT	30°		35°		35°	
ROTATION		DCG4	DCG6		DCG4	DCG6
		350°	354°		359°	354°
BEAM DISTRIBUTION		DCG4	DCG6		DCG4	DCG6
		90°	99°		113°	113°
CERTIFICATIONS						
	ETL Listed, Energy Star, Title 24, JA8, Title 20, Damp Location		ETL Certified, Energy Star, Title 24, JA8, Title 20, Damp Location		UL Classified, Energy Star, Title 24, Damp Location	
LIFESPAN (L70)	54,000 hours		56,000 hours		>36,000 hours	